

High Definition 5.1 Channel Home Theatre System



Consists of: 1 x RX-V465 1 x NS-P270

















High Sound Quality

- 5-channel powerful surround sound (525W=105W x 5 max for Europe, $525W = 105W \times 5 \text{ RMS}$, $675W = 135W \times 5 \text{ max}$)
- Decoders for HD audio formats: Dolby TrueHD and DTS-HD Master Audio; Dolby Digital Plus and DTS-HD High Resolution Audio
- Burr-Brown 192 kHz/24-bit DACs for all channels
- Direct Mode for high quality sound reproduction

High Picture Quality

- 1080p-compatible HDMI (4 in/1 out)
- Supports Deep Colour (30/36 bit), x.v.Colour, 120Hz/24Hz Refresh Rates and Auto Lip-Sync compensation

Advanced Features

- New SCENE buttons (BD/DVD, TV, CD and Radio) quick and simple to use
- YPAO sound optimisation for automatic speaker setup
- iPod compatibility via optional YDS-11 Universal Dock
- Bluetooth (A2DP) compatibility with optional Yamaha Bluetooth®
- iPod song titles displayed on the front panel
- HDMI CEC functionality
- New preset remote unit

Surround Realism

- CINEMA DSP (17 DSP programmes) with Adaptive DSP Level
- Adaptive DRC (Dynamic Range Control)
- Compressed Music Enhancer

NS-P270	Speakers
[Front Speakers]	2-way acoustic suspension
Dimensions (WxHxD)	105 x 151 x 113
Weight	0.8 kg
[Centre Speaker]	Full-range acoustic suspension
Dimensions (WxHxD)	300 x 72 x 113
Weight	0.9 kg
[Surround Speakers]	2-way acoustic suspension
Dimensions (WxHxD)	105 x 151 x 113
Weight	0.8 kg
NS-P270	Subwoofer
Output Power	100 W
Subwoofer Driver	16cm cone
Dimensions (WxHxD)	200 x 365 x 370
Weight	8.5 kg

YHT-392 AV Receiver (RX-V465)

Audio Section	
Maximum Output Power per Channel (For Europe, 4 ohms, 1	kHz, 0.7% THD)
Front L/R Channels	120 W/ch
Centre Channel	120 W
Surround L/R Channels	120 W/ch
Minimum RMS Output Power (6 ohms, 1 kHz, 0.9% THD)	
Front L/R Channels	105 W + 105 W
Centre Channel	105 W
Surround L/R Channels	105 W + 105 W
Maximum Power (6 ohms, 1 kHz, 10% THD)	
Front L/R Channels	140 W/ch
Centre Channel	140 W
Surround L/R Channels	140 W/ch
Dynamic Power/Channel (Front, 6/4/2 ohms)	105/130/150 W
Input Sensitivity/Impedance (1 kHz, 100 W/8 ohms, AV5)	200mV/47 k-ohms
Frequency Response (AV5, Front)	10 Hz-100 kHz +0, -3 dB

Output Level/Impedance	Rec Out	200 mV/1.2 k-ohms	
output Lever/impedance	Subwoofer	1 V/1.2 k-ohms	
Total Harmonic Distortion (AV5, 1 kH	z, 50 W/8 ohms)	0.06%	
Signal-to-Noise Ratio (AV5, 250 mV)		100 dB	
Video Section			
Video Monitor Out Frequency Respon	nse Component Video Signal	5 Hz-60 MHz -3 dB	
Tuner Section			
FM 50dB Quieting Sensitivity	Mono	3 μV (20.8 dBf)	
FM Signal-to-Noise Ratio	Mono / Stereo	74 dB / 69 dB	
General			
Standby Power Consumption		0.2 W (HDMI Control Off)	
Dimensions (W x H x D)		435 x 151 x 364 mm	
Weight		8.4 kg	

YDS-11 Universal Dock for iPod

iPod not included

The optional YDS-11 Universal Dock lets you connect your iPod to the receiver.





Yamaha Bluetooth® Wireless Audio Receiver

The optional YBA-10 Bluetooth Wireless Audio Receiver docks to the receiver and supports A2DP audio streaming, so users can enjoy music wirelessly from Bluetooth-enabled mobile phones, Windows PCs and Macs.



DOCK	HDMI DUT HDMI 2	5.585.674 AND WORI TRADEMAS COPYRIGHT	URED UNDER LICENSE UNDER U.S. PATENT NO S: 5.451.942: 5.5973,3801 5.5978,782: 6.226.515; 6.497,335 AND OTHER U.S. DVINCE PATENTS ISSUED AND PENDING. IDTS IS A REISSISTERED. K. AND THE OTS LOGIOS AND SYMBOLL AND FEBRICAMENTS OF DIS, INC. 1988-2010 71S; INC. ALL RIGHTS RESERVED. URED UNDER LICENSE FROM DUELY LABORATIONES. DOLBY, PRO LOGIC, URBLE-D SYMBOL ARE TRADEMARKS OF DOLBY LABORATORIES.
COMPONENT VIDEO PR VIDEO VIDEO	ANTENNA 750 UNBAL PR GND AM PB VIDEO VIDEO VIDEO	(S) FRONT (L) + (L)	SPEAKERS CENTER SURROUND (B) (C) (C)
OPTICAL COANIAL COANIA	MONITOR OUT MONITOR OUT AUGUS AUGU		SURROUND BACK SUBWOOFER

Extensive Connections

Inputs	
HDMI	4
Radio Antenna (FM/AM)	1 / 1
Dock Terminal for Optional Dock Accessories	1
Optical Digital (Fixed)	2
Coaxial Digital (Fixed)	2
Analog Audio*	5
Component Video (Fixed)	2
* Including front panel terminals	

4	Including	front	panel	termina	ls.

Outputs	
HDMI	1
Analog Audio	2
Pre Out (Surround Back L/R)	2ch
Component Video Monitor	1
Composite Monitor	1
Composite AV	1
Speaker (without subwoofer)*	5ch
Subwoofer	1

^{*} Banana-plug compatible speaker terminals are not available in some areas.

[•] iPod is a trademark of Apple Inc., registered in the U.S. and other countries. • The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. • Dolby and the double-D symbol are registered trademarks of Dis is a registered trademark and the DTS logos, Symbol, DTS-HD and DTS-HD Master Audio are trademarks of DTS, Inc. • HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. • Burr-Brown products are trademarks of Texas Instruments, Inc. • "x.v.Colour" is a trademark of Sony Corporation. • CINEMA DSP is a trademark of Yamaha Corporation. • SILENT CINEMA is a trademark of Yamaha Corporation. • Product designs and specifications are subject to change without notice.